$\Delta S \Delta - 4$ 4 x1 Audio Summer





The ASA-4, audio summer, will sum or mix up to 4 line level inputs and provides one transformer coupled line level audio signal output. The ASA-4 features unity gain which means no input signal is attenuated as happens in any passive mixing device. The residual noise (<80 db) insures that the fidelity of the incoming signals is not compromised in any way. The transformer coupling of the output insures that ground loop problems are completely eliminated.

The ASA-4 can handle both balanced and unbalanced inputs of both pro, semi-pro, and consumer audio sources. The unit is a 1/2 rack unit and comes complete with a rack mounting kit. This kit permits the installation of any two half rack units.

FEATURES:

- Active mixing no loading of inputs
- Four output trim controls (0 to +20dB)
- Pluggable screw terminal inputs and output
- Transformer coupled output drive long cables
- Metal case
- Rack mountable (1 rack unit high) mounting kit supplied

SPECIFICATIONS:

Audio Input Number/tvpe Connectors

Impedance

Max level

4 mono balanced or unbalanced 4 pluggable screw terminal 3 conductor 20k ohms DC coupled balanced, 10k ohm DC coupled unbalanced

+18 dBm (balanced or unbalanced) at stated % THD+N

Audio Throughput

Gain

Bandwidth THD+Noise

S/N

Stereo separation **CMRR**

Audio Output Number/type

> Connector Impedance Gain error

Drive

Unity with trim adjust to +20dB on each output

30 Hz to 20kHz (+/-0.5dB)

0.025% @ 1kHz at rated max. output

>90dB NA >80dB

> 1 transformer coupled (balanced/unbalanced)

1 pluggable screw terminal 3 conductor 600 ohm suitable for long cable drives

>+18dBm. balanced or unbalanced at

stated % THD+N

General Power Wall mount trans (27Vac @ 75ma)

Rack Mount Rack mount is supplied

Enclosure type Metal 1.75"H x 8.5"W x 4.75"D Enclosure dimensions

Weight 26 07.

UL and CSA Approvals

FSR Inc.

244 Bergen Boulevard, West Paterson, NJ 07424 Phone: 973.785.4347 · Fax: 973.785.4207 Web: www.fsrinc.com · E-mail: sales@fsrinc.com

ACCESSORIES:

A free rack mount kit is supplied with each ADA-4 unit. The black painted, steel rack mount kit allows for your choice of table or rack mounting without additional cost.

The wall mount transformer, also provided free with each unit, is 27VAC, @75ma, and is UL and CSA rated.





TYPICAL APPLICATION OF ASA-4



