

1. END CAP PIECE IS ONLY INSTALLED IN APPLICATIONS USING RACEWAY BASE EDGE #1, TYPICALLY WHEN MOUNTING THE RACEWAY BASE TO THE FINISHED FLOOR SURFACE. ALL OTHER APPLICATIONS, SKIP TO STEP 3.
2. IF THE END CAP IS REQUIRED, PASS THE END MOUNT TABS THROUGH THE END CAP SLOTS, ASSEMBLING THEM AS SHOWN BELOW.
3. SLIP THE END MOUNT TABS INTO THE TRACK END, AND MAKE SURE THE END MOUNT OR ASSEMBLY IS PUSHED DIRECTLY AGAINST THE RACEWAY BASE END.
4. INSTALL SUPPLIED SCREWS INTO THE END MOUNT TAB TAPS, AND TIGHTEN THEM TO SECURELY CAPTURE END MOUNT/ASSEMBLY.

Classification; CTS/DTS 3.102 Flushfloor, 3.103 Onfloor, 6.101.1 Dry-Treatment Only, 6.2.7 20J Impact, 6.102.7 3,000 N Small Surface Load, 6.103.5 15,000 N Large Surface Load, 6.4.1 Non-Flame Propagating IP41; Min Storage Temp - 25°C; Installation and Application Temp - 15°C to 60°C; 0.001 Ω/m

CAUTION: ENSURE EDGE OF RACEWAY COVER IS DEBURRED.

