




FSR HUDDLY CAMERA MOUNT INSTALLATION INSTRUCTIONS

244 Bergen Boulevard, Woodland Park, NJ 07424, Phone: 973.785.4347 - FAX 973.785.4207



HUDDLY CAMERA MOUNT INSTALLATION:

HUDDLY CAMERA MOUNT CAN BE ORIENTED TO ALLOW CAMERA TO MOUNT ABOVE OR BELOW THE VESA MOUNT MONITOR AND IS COMPATIBLE WITH THE FOLLOWING VESA MOUNT SIZES:

- 200 X 200
- 300 X 200
- 300 X 300
- 400 X 200
- 400 X 300
- 400 X 400

NOTICE: ENSURE THE DISTANCE FROM THE TOP HOLE OF THE VESA FOOTPRINT TO THE TOP EDGE OF THE MONITOR WHEN USING THE "ABOVE MONITOR MOUNT" CONFIGURATION, OR FROM THE BOTTOM HOLE OF THE VESA FOOTPRINT TO THE BOTTOM EDGE OF THE MONITOR WHEN USING THE "BELOW MONITOR MOUNT" CONFIGURATION, IS LESS THAN 13.25".

1. INSTALL HUDDLY CAMERA ON CAMERA PERCH, USING 1/4" NYLON WASHER AND 1/4-20 ADAPTER PROVIDED.
2. INSTALL MOUNT AND PIVOT BRACKET BETWEEN THE MONITOR AND VESA MOUNT BRACKETS, IN DESIRED ORIENTATION, USING THE ORIGINAL HARDWARE AS SHOWN ABOVE. DO NOT FULLY TIGHTEN AT THIS TIME.
3. USE NYLON WASHERS PROVIDED TO SHIM OUT THE SPACE BETWEEN THE MONITOR AND VESA MOUNT BRACKETS ON THE REMAINING TWO MOUNTING HOLES. FOLLOW INSTRUCTIONS PROVIDED WITH VESA MOUNT BRACKETS, TO FINISH INSTALLING TO THE MONITOR.
4. WITH VESA MOUNT HARDWARE STILL LOOSE, SLIDE THE MOUNT AND PIVOT BRACKET UNTIL THE CAMERA IS CLOSE TO THE SURFACE OF THE MONITOR. LEAVE ROOM FOR CAMERA PERCH ANGLE ADJUSTMENT. TIGHTEN THE REMAINING VESA MOUNT HARDWARE.
5. FOLLOW INSTRUCTIONS PROVIDED WITH VESA MOUNT TO INSTALL THE MONITOR ON THE WALL.
6. INSTALL CAMERA AND CAMERA PERCH TO MOUNT AND PIVOT BRACKET USING #6-32 X .375. ENSURE ANGLE FOR CAMERA IS CORRECT BEFORE TIGHTENING.