



CABLE PILOT CABLE SPECIFICATIONS



Cable Pilot USB-C Cable Specs

Technical Parameters	3 Meter Cable	4 Meter Cable (Silver)
Classification	USB 3.2 Gen 1x2	USB 3.2 Gen 1x2
Peripheral Supported Data type	USB 2.0, USB 1.1	USB 2.0, USB 1.1
Maximum data speed	10 Gbps (5 Gbps/lane)	10 Gbps (5 Gbps/lane)
Display Port alternate mode	Yes, HBR2, 2-4-lane	Yes, HBR2, 2-4-lane
Video Format	Up to 4096×2160@60Hz at RGB 4:4:4 and 5120×2160@30Hz at RGB 4:4:4	Up to 4096×2160@60Hz at RGB 4:4:4 and 5120×2160@30Hz at RGB 4:4:4
Rated voltage	20 V	20 V
Rated current	5 A	5 A
Physical Parameters	3 Meter Cable	4 Meter Cable (Silver)
Connectors	2 × USB Type-C male	2 × USB Type-C male
Length	3 m	4 m
Cable diameter	5.9 mm	5.4 mm
Jacket material	TPE	TPE
Wire material	Copper	Silver Coax
Mold material	Aluminum/PVC	Aluminum/PVC
Pin coating	Gold-plated	Gold-plated
Color	Black	Black



Cable Pilot HDMI Cable Specs

Technical Parameters	3 Meter Cable	4 Meter Cable
Classification	High Speed HDMI 2.0	High Speed HDMI 2.0
Maximum data speed	4K 18 Gbps	4K 18 Gbps
Video Format	Up to 4096×2160@60Hz at RGB 4:4:4 and 5120×2160@30Hz at RGB 4:4:4	Up to 4096×2160@60Hz at RGB 4:4:4 and 5120×2160@30Hz at RGB 4:4:4
Ethernet Capable	Yes	Yes
ARC Capable	Yes	Yes
Physical Parameters	3 Meter Cable	4 Meter Cable
Connectors	2 × HDMI male	2 × HDMI male
Length	3 m	4 m
Cable diameter	6 mm	6 mm
Jacket material	TPE	TPE
Wire material	Copper	Copper
Shield	70% Braid Over Foil	70% Braid Over Foil
Mold material	PVC	PVC
Pin coating	Gold-plated	Gold-plated
Color	Black	Black



244 Bergen Boulevard, Woodland Park, NJ 07424
 Phone: 973.998.2300 · Fax: 973.785.4207
 Web: www.fsrinc.com · E-mail: sales@fsrinc.com