



FEATURES OF NEW CB-224 CEILING BOX:

- DEEPER BOX DESIGN TO CARRY PULL-DOWN 4-RU RACK CAGE THAT IS 12" LONG, AND CAPABLE OF CARRYING 25lbs OF ELECTRONIC EQUIPMENT.
- PULL-DOWN 4-RU RACK CAGE IS GAS-SPRING DAMPED ON DOWN-TRAVEL, AND LIFT-ASSISTED ON UP-TRAVEL.
- 2RU OF ANGLE-ADJUSTABLE RACK-MOUNTING SURFACES, ON EITHER END OF THE RACK CAGE, TO FACILITATE MOUNTING AND VISIBILITY OF 1RU/2RU PATCH PANELS.
- 1-3/8" CLEAR SPACE ON BOTH SIDES OF RACK CAGE WHEN INSIDE THE BOX, TO ALLOW FOR WIRE BUNDLES TO TRAVERSE PARALLEL TO THE RACK CAGE AFTER INSTALLATION.
- EDGE-PROTECTED BUNDLED-CABLE-INLET CAVITY EACH SIDE OF THE BOX, FILLED WITH FLAME-RETARDANT FOAM SEAL.
- 1"/1.25"/1.50"-TRADE-SIZE KNOCKOUTS, ONE SET PER SIDE OF THE BOX, WITH (2) 0.5"/.75"-TRADE-SIZE KOs FOR LINE-VOLTAGE WIRING TO THE INCLUDED (6) OUTLETS.
- AVAILABLE IN 4 VERSIONS: NON-POLE MOUNT AND POLE-MOUNT, BOTH WITH OR WITHOUT 'SMART' ELECTRONICS.

