

TwisterPro

UTP Transmitter/Receiver System

FSR

Video Products Group

TwisterPro



DESCRIPTION

The TwisterPro™ UTP Transmitter / Receiver System allows video, stereo audio, RS-232 data and IR signal transmission over ordinary low cost CAT-5, 5e, 6 and cable. This system offers the highest level of signal integrity. These high quality devices ensure reliable, error free transmission that is immune to interference from electrical noise. Cable runs of up to 1000 feet are within the capabilities of the system (see specs for maximum cable length details).

There are wall plate style transmitters (1-gang and 2-gang) and receivers (2-gang) offered in three colors; black, white, and ivory. Matching Decora™ trim rings are included for stand alone use, or the units be populated along with FSR's IPS component and plates for a complete interface solution. There are also "brick" style housing versions that can be used on any surface or rack mounted using the accessory rack kits if preferred. (See TwisterPro™ accessories and ordering info).

TPRO receivers with skew compensation adjustments are optional and help adjust for mis-convergence of the red, green and blue video signals that can occur as a result of inherent delay caused by differences in cable twist lengths.

The system can be powered at either the transmitter or receiver end by the optional power supply(s). If a TPRO- HUB is used, the hub with it's included power supply, will power the other components in the system. This 1 in 8 out hub allows full expandability for demanding applications. Multiple hubs can be cascaded to achieve a maximum of 512 outputs.

FEATURES

RGB Video Transmission system

- HD-15 female connectors for video input and output
- CAT-5 connections are via RJ-45 Connectors (EIA/TIA-568B)
- Video resolutions up to 1920 x 1080 (1080p)
- Cable skew compensation adjustments on -S model receiver
- Adjustable gain control on front panel

RS-232 Data Transmission

- DB-9 female connectors for the inputs and male for outputs (optional for TPRO-TX wallplate models)
- UTP connections are via RJ-45 Connectors (EIA/TIA-568B)
- Compatible with RS-232 standards
- UL and CSA approved external power source (wall plug-in)
- Simplex RS-232 up to 19.2k baud
- LED indication of RS232 data activity

IR Control Data Transmission

- Compatible with most IR devices
- Custom carrier frequencies are available per customer request
- Extends IR control up to 1000 feet
- Normal and high output emitter power level settings
- High output power level settings up to 60mW allows for multiple emitter connections - (emitters sold separately)
- Transmitters feature integrated IR sensors in addition to hard-wired input options
- LED indication of IR data activity

General

- Units can be powered at either end or through optional hub
- Over-current sensing with LED indication
- Video, RS-232 and IR LED indicators
- Optional 1 in 8 out TPRO-HUB with power supply available

APPLICATIONS

- Boardrooms
- Houses of Worship
- Control Rooms
- Classrooms
- Digital Signage
- Hotel/Conference Facilities
- Temporary Staging and Rental

FSR Inc.

244 Bergen Boulevard, Woodland Park, NJ 07424

Phone: 973.998.2300 · Fax: 973.785.4207

Web: www.fsrinc.com · E-mail: sales@fsrinc.com

LIT 1283E

TwisterPro ORDERING INFORMATION

TwisterPro requires a Transmitter (choose your preference), a Receiver (choose your preference), and Power Supply. No power supply is needed if you are connecting to the TwisterPro Hub.

TwisterPro Wall Plate Transmitters - Includes Decora Trim Ring

Item #	Part #	Description
16991	TPRO-TXWP-BLK	1 Gang Decora PC Video, St Aud, IR Transmitter Wall Plate - Black
16992	TPRO-TXWP-WHT	1 Gang Decora PC Video, St Aud, IR Transmitter Wall Plate - White

TwisterPro 1RU x 1/4 Wide Brick Transmitter

16998	TPRO-TXD	PC Vid, St Aud, IR and Serial Transmitter 1 RU x 1/4 Wide
-------	----------	---

TwisterPro Wall Plate Receiver - Includes Decora Trim Ring

17009	TPRO-RXWPD-BLK	2 Gang Decora PC Video, St Aud, IR, Serial Receiver - Black
17012	TPRO-RXWPDS-BLK	2 Gang Decora PC Vid, St Aud, IR, Ser and Skew Comp Rx - Black

TwisterPro 1RU x 1/4 Wide Brick Receiver

17015	TPRO-RXD	PC Vid, St Aud, IR, Serial Receiver 1 RU x 1/4 Wide
17016	TPRO-RXDS	PC Vid, St Aud, IR, Serial and Skew Comp Receiver 1 RU x 1/4 Wide

TwisterPro Power Supply

15552	PS-24DC-500MA	24VDC 500ma Power Supply
-------	---------------	--------------------------

TwisterPro Hub

17017	TPRO-HUB	1 in 8 Out Hub with Power Supply
-------	----------	----------------------------------

TwisterPro Accessories

17019	IR-EC1-6	Single Head IR Emitter w/ 3.5mm Jack
15773	SS-P1DB-WHT	White Insert punched w/ 1 9-Pin D-Sub Hole
15775	SS-P1DB-BLK	Black Insert punched w/ 1 9-Pin D-Sub Hole
15706	SS-DPLT2-WHT	White Double Gang Decora Wall Plate
15708	SS-DPLT2-BLK	Black Double Gang Decora Wall Plate
16808	RK-1	1/4 and 1/2 Rack Mounting Kit
16809	RK-2	1/4 and 1/2 Rack and Module Mounting Shelf

TECHNICAL SPECIFICATIONS

RGB VIDEO INPUT		
Connector	1-HD-15 female connector	
Signal Type	1 RGBHV, RGBS, RGsB, RsGsBs, Component, S-video or Composite	
Maximum Resolution	1920 X 1080 (1080P)	
Impedance	75Ω	
Level (nominal)	Analog 0.7V p-p	
Level (maximum)	+-1.0 V	
RGB VIDEO OUTPUT		
Connector	1-HD-15 female connector (Brick models have an additional HD-15 loopback connector)	
Signal Type	Same as input	
Gain	Unity	
Impedance	75Ω	
Sync output	5V into Hi Z, 2.2V into 75Ω	
AUDIO INPUT		
Connector	1-3.5 mm stereo mini jack (wallplates), 3 pin Phoenix plug (bricks)	
Signal type	Stereo unbalanced	
Level (nominal)	0.25V RMS -10dBm	
Level (maximum)	1.1V RMS, +3dBm	
Impedance	50 kΩ	
Encoding	Full stereo 24 bit, 96kHz sample rate	
Frequency response	20Hz-15kHz +-0.5dB	
AUDIO OUTPUT		
Connector	Wallplate model receivers	2 RCA jack connectors
	Brick model receivers	3 pin pluggable screw terminals
Signal type	Stereo unbalanced	
Impedance	50Ω (Intended to drive a 600Ω or greater load)	
Gain	Unity +- 1.5dB	
CONTROL ADJUSTMENTS		
Delay Adjust	Independent for R, G and B delay (Skew models only)	
Delay range	0-62 ns (Skew models only)	
Video Boost Switch	Dip switch (OFF 0-800'/ON 200-1000')	
Gain control	Manual combined control for RGB	
RS-232 DATA INPUT		
Number/Type	One DB-9 female connector, (4 pin Phoenix plug on brick models) DCE type connection for direct connection to a PC serial port included on two gang transmitters only. Must order TPRO-Serial DB-9 accessory harness for one gang transmitters.	
Handshaking	Local loopback only (Models with DB-9 connectors only)	
RS-232 type	Unidirectional (data transmission from transmitter to receiver only)	
RS-232 DATA OUTPUT		
Number/Type	One DB-9 male connector. DTE type connection for direct connection to peripheral.	
Data Rate	0-19.2k baud	
INFRARED INPUT		
Number/Type	Both models have internal sensor logically OR'd with hardwired input.	
	T-PRO TX brick models	One 4 pin pluggable Phoenix connector
	T-PRO-TX wallplate models	One C-grid SL 5-pin connector on the back of the unit.
Compatibility	Compatible with most IR outputs designed to drive an IR emitter LED.	
INFRARED OUTPUT		
Number/Type	One 3.5 mm mini jack, center positive. All TPRO-RX models (Use FSR IR-EC1-6 single or IR-EC2-6 dual emitter accessory.)	
Output Switch	Dip switch (Normal 12 mW/High 60mW)	
Carrier Range	40 kHz, custom frequencies available per request.	
POWER REQUIREMENTS		
TPRO-RX Receivers	24VDC@0.12A (Skew models are 24VDC@0.19A)	
TPRO-TX Transmitters	24VDC@0.09A	
	Power supplies are optional. Use FSR PS-24DC-500MA	
MECHANICAL		
Transmitter enclosure	Model	Dimensions (inches)
	Brick	4.22 X 1.59 X 4.10
Receiver enclosure	Model	Shipping weight lbs.
	Wall plate	1.70 X 4.09 X 1.46
Receiver enclosure	Brick	4.22 X 1.59 X 4.10
	Wall plate	3.56 X 4.09 X 1.29
GENERAL		
UTP cable wiring standard/ type	EIA / TIA-568B CAT5, 5E, 6	
Recommended transmission range	0-1000 ft with a single power supply (Up to 600' when powered at transmitter. Up to 1000' when powered at receiver. When using a TPRO-HUB with included power supply: The maximum distance to a transmitter is 1000'. The maximum distance to a receiver is 600' * * A distance of up to 1000' can be achieved by adding an additional power supply at the receiver	



Specifications are subject to change without notice.



244 Bergen Boulevard, Woodland Park, NJ 07424
 Phone: 973.998.2300 · Fax: 973.785.4207
 Web: www.fsrinc.com · E-mail: sales@fsrinc.com