

SS-USB-CHRG-PS6

Distribution for DC Powered USB Chargers



Power Products Group



DESCRIPTION

The SS-USB-CHRG-PS6 is a remote power solution for the FSR IT-USB-CHRG, SS-USB-CHRG, *SS-USB-C-CHRG and IPS-D717S DC Powered USB Chargers; It consists of a rack mounted board to remotely power up to six (6) DC Powered USB Chargers and a 15 VDC@ 6 A power supply with AC power cord. The unit provides an inexpensive means of neatly distributing USB power from an included single power supply, eliminating the need for multiple AC wall adapters and messy overloaded power strips.

***Limit SS-USB-C-CHRG chargers to 5 if you are likely to have simultaneously connected devices.**

AWG	MAXIMUM LENGTH (FT.)
22 AWG	60 feet
20 AWG	100 feet
18 AWG	150 feet
NOTE: Maximum length limits may be doubled if using only five SS-USB-CHRG chargers or if a maximum of five will be loaded at the same time.	

Photos and illustrations are not to scale.

FEATURES

- 1-RU (1.75") high, low-voltage distribution board
- Two mounting holes are provided to attach to the rear rack rails in a rack
- Rear of PCB should be covered (black foam tape may be used)
- All connections are via captive-screw terminals
- Power supply is included to handle up to 6 remote FSR DC Powered USB Chargers.
- On-Board LED power indicator
- Inexpensive solution for remote USB power distribution

COMPATIBLE DC CHARGER PLATES



IT-USB-CHRG

- Wall Plate DC to USB charger



SS-USB-CHRG

- Keystone DC to USB charger



IPS-D717S

- IPS DC to USB charger
- Keystone snap-in charging port compatible with USB-C® devices



SS-USB-C-CHRG

- Keystone snap-in charging port compatible with USB-C® devices
- Available in Black


FSR Inc.

244 Bergen Boulevard, Woodland Park, NJ 07424
Phone: 973.998.2300 · Fax: 973.785.4207
Web: www.fsrinc.com · E-mail: sales@fsrinc.com
Toll Free: 1-800-332-FSR1

LIT1483D

SPECIFICATIONS

Photos and illustrations are not to scale.





TWO CONDUCTOR HOOK-UP WIRE (INSTALLER PROVIDED). TWO OHM MAXIMUM ROUND TRIP. SEE CHART FOR LENGTH VS. GAUGE REQUIREMENTS.

OBSERVE POLARITY AS INDICATED ON THE SS-USB-CHRG-PS6 AND THE CHARGER PLATES.

AWG	MAXIMUM LENGTH (FT.)
22 AWG	60 feet
20 AWG	100 feet
18 AWG	150 feet

NOTE: MAXIMUM LENGTH LIMITS MAY BE DOUBLED IF USING ONLY FIVE SS-USB-CHRG CHARGERS OR IF A MAXIMUM OF FIVE PORTS WILL BE IN USE AT THE SAME TIME.



244 Bergen Boulevard, Woodland Park, NJ 07424
Phone: 973.998.2300 · Fax: 973.785.4207
Web: www.fsrinc.com · E-mail: sales@fsrinc.com



Specifications are subject to change without notice.