CB + MLS Series

Ceiling Boxes with Pre-wired Modular Linx System





CB-224-MLS



Build America Buy America Act (BABAA) and TAA requirements

DESCRIPTION.

With the MLS pre-wired ceiling boxes, the electrical contractor can install and power the MLS starter cable at any time during the initial construction phase. The CB-MLS eliminates coordinating return visits to the site to connect AC to the ceiling box after the AV contractor completes hanging the unit. The AV contractor will now be able to complete the AV install without multiple trips to the site. They can mount the unit, install the AV equipment, wire, and test without waiting for the electrical contractor to connect the AC to the mounted, empty ceiling box.

FEATURES

- Pre-wired ceiling box with MLS 2' drop cable
- Provides the ability to install and power at the beginning of the construction phase
- Eliminate return visits to connect power after ceiling box is mounted
- Mount, install equipment, wire, and test all in one visit
- CB-MLS saves time and money

ORDERING INFORMATION

18537	CB-12-MLS	1' x 2' MLS - Prewired with 5 AC Outlets
18538	CB-12P-MLS	1' x 2' with Pole -MLS - Prewired with 5 AC Outlets
18539	CB-22-MLS	2' x 2' MLS - Prewired, 6 Unswitched Outlets
18540	CB-22P-MLS	2' x 2' with Pole, MLS - Prewired, 6 unswitched outlets
18541	CB-22S-MLS	2' x 2' Smart, MLS - Prewired, 6 outlets, 4 switched
18542	CB-22SP-MLS	2' x 2' Smart, Pole, MLS - Prewired, 6 outlets, 4 switched
18543	CB-224-MLS	2' x 2' MLS - Prewired, 6 unswitched outlets
18544	CB-224P-MLS	2' x 2' with Pole MLS - Prewired, 6 unswitched outlets
18545	CB-224S-MLS	2' x 2' Smart, MLS - Prewired, 6 outlets, 4 switched
18546	CB-224SP-MLS	2' x 2' Pole, Smart, MLS - Prewired, 6 outlets, 4 switched
18485	MLS-2SC-4	Starter Cable 4'
18486	MLS-2SC-6	Starter Cable 6'

FSR Inc.

244 Bergen Boulevard, Woodland Park, NJ 07424 Phone: 973.998.2300 · Fax: 973.785.4207 Web: www.fsrinc.com · E-mail: sales@fsrinc.com

Order Desk: 1-800-332-FSR1

FIELD TERMINATIONS FOR MLS STARTER CABLES AND INPUT SOCKETS FOR CEILING BOXES WITH MLS INPUT

MLS Input Devices 4-12 Gauge Wires, L1,L2,N,G 125V 20A























