T3-AC2

Table Boxes


US Patent US D553.306 S







Metal Products Group



DESCRIPTION

The T3-AC2 primarily allows quick, convenient access to AC power and network access for up to two computers or laptops.

The keystone areas can be populated with a variety of connectors including network, telephone, RCA or mini stereo audio, push buttons and much more to suit unlimited applications. Alternate style snap in keystone connectors and blanks are available separately.

These stylish table boxes fit a 3½" round opening and are easily installed using a standard hole saw.

Round covers are available in black, brass or aluminum to blend with the decor. The small footprint provides an unobtrusive complement to any décor. The T3-AC2 can be installed in tables ¾" to 2½" thick. They are shipped with 3" installation screws and the components listed below.

The T3-AC2 includes:

- 2 AC Power outlets (pre-mounted) with 9' integral
 14 GA SJT power cord
- The T3-AC2HW hardwired versions do not include a power cord. Short leads and wire nuts are provided for direct AC connection.
- · 2 RJ-45 pass through connector (pre-mounted)

APPLICATIONS

- Desks
- Lecterns
- Lab Tables
- Boardroom Tables
- Control Consoles
- Classrooms

FEATURES.

- Round Covers
- Can be matched to nearly any décor with Black, Aluminum or Brass Top
- Easy and flexible installation 3½" Hole ¾" to 2½" table thickness
- · Can be easily configured to match customer needs
- Built to Last CNC Milled Solid Cover Rugged 16 gauge-galvanized steel Chassis Cable Strain Relief Attach Point
- No Annoyance Factor
 Cover Opens 96 Degrees so it Stays Open
 Rubber Grommets for quiet closure

T3-AC2/T3-AC2HW

Top view shown with round cover
(2) RJ45 Pass- Thru
Snap-In Connector

(2) AC Outlet,
12A MAX.

4.25

4.25

#6 - #8
Mounting
Screw Holes


6.20

FSR Inc.


244 Bergen Boulevard, Woodland Park, NJ 07424 Phone: 973.998.2300 · Fax: 973.785.4207 Web: www.fsrinc.com · E-mail: sales@fsrinc.com

Toll Free: 1-800-332-FSR1

T3-AC2 Assembly



T3-AC2HW Assembly



- 1) Install clamp shroud to underside of table hole with (5) wood screws as shown. Orient per desired cover swing direction.
- (2) Place the "T3-AC2HW" sub-assembly into the hole in the table (cover orientation is pre-set by the shroud installation).
- (3) Pass the desired length (2) long screws thru the shroud and thread into short standoffs in the sub-ass'y. Turn the 3/8" long clamps nuts up snug against the shroud baseplate to pull the sub-ass'y down completely into place in the pre-cut 3.50" dia. hole.
- (4) Make electrical connections and tie-wrap cables to tie-tabs as required. Ensure enclosed end of wire nuts face receptacles.

ORDERING INFORMATION.

T3-AC2 3.5" Round Table Box		
16267	T3-AC2-BLK	2 A/C and 2 Keystone Connectors - Plug - Black - Round cover
16758	T3-AC2-BLK-CAT6	2 AC and 2 CAT6 Connectors - Plug - Black - Round cover
17098	T3-AC2HW-BLK	2-Power, 2-Data 3.5" - Hardwired - Black - Round cover
16266	T3-AC2-ALM	2 A/C and 2 Keystone Connectors - Plug - Aluminum - Round cover
17097	T3-AC2HW-ALM	2-Power, 2-Data 3.5" - Hardwired - Aluminum - Round cover
16268	T3-AC2-BRS	2 A/C and 2 Keystone Connectors - Plug - Brass - Round cover
17099	T3-AC2HW-BRS	2-Power, 2-Data 3.5" - Hardwired - Brass - Round cover





