SmartFit
6” Fire-Rated Poke-Thru

FIRE RATED

FSR floor box products meet the Build America Buy America Act (BABAA) and TAA requirements

FSR Metal Products Group





c UL us

DESCRIPTION

FSR’s new Fire-Rated “Poke-Thru” floor boxes provide capacity, aesthetics and installation ease. These sturdy core hole products combine flexibility via recessed mounting bracketry to accommodate a wide assortment of power, data and audio video connection options.

Covers are available in three architectural finishes: Brushed Aluminum, Black and Brushed Brass, providing an attractive appearance with superior durability. The entire cover door swings open 180° and the two smaller cable access doors fold down for cable egress while the cover door is secure.

A complete line of sub-plates for device mounting is available. The mounting plates incorporate a unique industry first 60/40 & 50/50 layout for un-paralleled capacity and flexibility; including twelve CAT 6 data jacks and two or four 20A AC receptacles. The cover technology exceeds UL scrub water testing requirements.

SPECIFICATIONS


- *2-hour fire rating*
- *180˚ access door opening*
- *Flange height 0.15” and complies with ADA requirements*
- *Power wiring junction box included*
- *Complies with UL514A for scrub water test*
- *1000 lb. cover load rating with 2x safety factor*
- *ULC and cULus*

FEATURES


- *Drop down cable access doors to reduce trip hazards*
- *Furniture feed option (6” core hole) for up to thirty CAT 6a data cables and ten 10 AWG power wires*
- *Pre-pour tubes remove the need for core hole drilling*
- *Sub-plates accept IPS Plates and third party devices*

All Fire-Rated Poke-Thru’s are Buy American compliant


OVERALL DIMENSIONS




SF6-ABAND
Abandonment Cover



Furniture Feed
Cover














SF6-CVR



FSR Inc.
244 Bergen Boulevard, Woodland Park, NJ 07424
Phone: 973.998.2300 · Fax: 973.785.4207
Web: www.fsrinc.com · E-mail: sales@fsrinc.com
Toll Free: 1-800-332-FSR1

Item #	6” Poke-thru without cover
SF6-PT	 Poke thru, no sub plates, no cover

Item #	Complete 6” Poke-Thru with Cover and Sub-Plates Shown	
SF6-CPT-DD-ALM SF6-CPT-DD-BLK SF6-CPT-DD-BRS		Includes: 6” floor fitting, Dual Decora opening subplate, Dual 20A pre-wired AC outlet subplate, Cover Assembly Junction box
SF6-CPT-AVD-ALM SF6-CPT-AVD-BLK SF6-CPT-AVD-BRS		Includes: 6” floor fitting, One Decora and two keystone opening subplate, One 5-IPS subplate, One 3-AAP subplate, Four 20A pre-wired AC outlet subplate, Cover Assembly, Junction box
SF6-CPT-FF-ALM SF6-CPT-FF-BLK SF6-CPT-FF-BRS	 One piece 6” for Furniture Feed	Includes: 6” floor fitting, 2” conduit fitting for data and AV, 3/4” conduit fitting for power, Cover Assembly, Junction box
	6” Covers Only	
SF6-CVR-ALM SF6-CVR-BLK SF6-CVR-BRS		

Item #	6” Optional Parts 60/40 Split
SF6-SPLL1	 One decorator opening with two IPS openings (left plate)
SF6-SPLL2	One decorator opening with two Extron® AAP openings (left plate) 
SF6-SPLL3	 Two decorator opening sub-plate (left plate)
SF6-SPSR1	Two 20A pre-wired receptacles with 16” wire lead (right plate) 
	6” Optional Parts 50/50 Split
SF6-SPL4	 Blank cover plate sub-plate (left plate)
SF6-SPL5	One decorator and two keystone openings (left plate) 
SF6-SPL6	 Three IPS 2 keystone jacks (left plate)
SF6-SPL7	One decorator opening (left plate) 
SF6-SPL8	 Five IPS openings (left plate)
SF6-SPL9	Three AAP openings (left plate) 
SF6-SPR2	 1.56” opening for Twist-Lock sub-plate (right plate)
SF6-SPR3	Single duplex device opening sub-plate (right plate) 
SF6-SPR4	 1.39” opening for Twist-Lock sub-plate (right plate)
SF6-SPR5	Single decorator device opening sub-plate (right plate) 
SF6-SPR6	 Four pre-wired power cubes with 16” wire lead (right plate)
	Accessories 
SF6-PS	6” pre-pour sleeve
SF6-ABAND	Abandonment for 6” core hole cover 

MADE IN THE USA

GREEN

Specifications are subject to change without notice.

FSR

244 Bergen Boulevard, Woodland Park, NJ 07424· Phone: 973.785.4347 · Fax: 973.785.4207
Web: www.fsrinc.com · E-mail: sales@fsrinc.com